

# Romiley Board Mill

## Unlined Chipboard Specification

Thickness mm	Nominal GSM	Bulk	Moisture (+/- 1%)
0.500	350	1.43	6%
0.525	362	1.45	6%
0.550	373	1.47	6%
0.575	384	1.50	6%
0.600	396	1.52	6%
0.625	413	1.51	6%
0.650	429	1.52	6%
0.675	446	1.51	6%
0.700	462	1.52	6%
0.725	479	1.51	6%
0.750	495	1.52	6%
0.775	512	1.51	6%
0.800	528	1.52	6%
0.825	545	1.51	6%
0.850	561	1.52	6%
0.875	578	1.51	6%
0.900	594	1.52	6%
0.925	611	1.51	6%
0.950	627	1.52	6%
0.975	644	1.51	6%
1.000	655	1.53	6%
1.025	671	1.53	6%
1.050	688	1.53	6%
1.075	704	1.53	6%
1.100	721	1.53	6%
1.125	737	1.53	6%
1.150	753	1.53	6%
1.175	770	1.53	6%
1.200	786	1.53	6%
1.225	802	1.53	6%
1.250	819	1.53	6%
1.275	835	1.53	6%
1.300	851	1.53	6%
1.325	867	1.53	6%
1.350	883	1.53	6%
1.375	899	1.53	6%
1.400	915	1.53	6%

Grammage +/- 5%      Moisture +/- 1%      Minimum Reel Slit 75mm

Thickness +/- 5%      Maximum Reel Slit 2090mm

Unlined Chipboard Specification

### Romiley Board Mill

Canalside Buildings, Oakwood Road, Romiley,  
Stockport, Cheshire, SK6 4DZ, ENGLAND.

Tel: (+44) 0161 430 6061

Email: sales@romileyboard.co.uk

www.romileyboard.co.uk

Part of Preston Board & Packaging Group



Company Reg: 1567779